

FI-X SERIES CONNECTORS

1.00mm (.039") Contact Spacing, Connector for PCB-to-Cable

MATERIALS AND FINISHES, Cont.

FI-X**M(R) (Cable Connector, FPC Relay Type)

Ground Plate	Copper Alloy / Tin plating
Insulator	Glass filled 4-6 Nylon (UL94V-0, Beige)
Shell	Copper Alloy/Tin plating
Slider	Thermal Plasticity plating
Contact	Copper Alloy: Contact Portion: Gold plating over Nickel FPC Contact Portion: Tin-Lead plating over Nickel

FI-XC3-1-15000 (Socket Contacts)

Contact	Copper Alloy: Contact Portion: Gold plating over Nickel Cable Crimping Portion: Tin plating
---------	---

FI-X**H (Cable, Crimp Housing)

Description	Materials/Finishes
Housing	Glass filled 4-6 Nylon
Shell	Copper Alloy/Tin plating (D7: Gold plating over Nickel on ground)

FI-X**C (Cable Connector)

Ground Plate	Copper Alloy / Tin plating
Insulator	Glass filled 4-6 Nylon
Slider	Thermal Plasticity plating
Contact	Copper Alloy: Contact Area: Gold (0.1µm min.) over Nickel Terminal Area: Tin-Lead over Nickel

TOOLING

Description	Part Number
Hand Crimp Tool	CT150-4C-FIX
Press	CP215-4B
Applicator	350-FI-2B

ORDERING INFORMATION

