

POLYPROPYLENE INSULATED END SLEEVES PKD

for flexible copper cables



The PKE, PKC, CPKD range of end sleeves is manufactured from tin plated electrolytic copper. Designed and developed to reinforce fine wire strands when terminating a cable into a connector block.



Technical characteristics

Min operating temperature range	-20 °C
Max operating temperature range	105 °C
Max operating temperature range (surge)	110 °C
Halogen Free	yes
Material (Body)	Tinned electrolytic copper electrolytically
Material (Partially reinforced)	Polyamide PA6.6

Media gallery



Attachments




[DATASHEET](#)

List of products




PKD Cable type: flexible copper, Maximum section: 0.75 mm²




Type	Colour	Ø	B	P	L	Pack qty	Min. pack qty
PKD7506	Grey	2.8 mm	1.6 mm	6 mm	12 mm	10,000	500
PKD7508	Grey	2.8 mm	1.6 mm	8 mm	14 mm	10,000	500
PKD7510	Grey	2.8 mm	1.6 mm	10 mm	16 mm	10,000	500
PKD7512	Grey	2.8 mm	1.6 mm	12 mm	18 mm	10,000	500

PKD Cable type: flexible copper, Maximum section: 1 mm²




Type	Colour	Ø	B	P	L	Pack qty	Min. pack qty
PKD106	Red	3 mm	1.8 mm	6 mm	12 mm	10,000	500
PKD108	Red	3 mm	1.8 mm	8 mm	14 mm	10,000	500
PKD110	Red	3 mm	1.8 mm	10 mm	16 mm	10,000	500
PKD112	Red	3 mm	1.8 mm	12 mm	18 mm	10,000	500

PKD Cable type: flexible copper, Maximum section: 1.5 mm²




Type	Colour	Ø	B	P	L	Pack qty	Min. pack qty
PKD1508	Black	3.5 mm	2.1 mm	8 mm	14 mm	5,000	500
PKD1510	Black	3.5 mm	2.1 mm	10 mm	16 mm	5,000	500
PKD1512	Black	3.5 mm	2.1 mm	12 mm	18 mm	5,000	500
PKD1518	Black	3.5 mm	2.1 mm	18 mm	24 mm	5,000	500

PKD Cable type: flexible copper, Maximum section: 2.5 mm²




Type	Colour	Ø	B	P	L	Pack qty	Min. pack qty
PKD2508	Blue	4.2 mm	2.6 mm	8 mm	14 mm	5,000	500
PKD2512	Blue	4.2 mm	2.6 mm	12 mm	18 mm	5,000	500
PKD2518	Blue	4.2 mm	2.6 mm	18 mm	24 mm	5,000	500

PKD Cable type: flexible copper, Maximum section: 4 mm²




Type	Colour	Ø	B	P	L	Pack qty	Min. pack qty
PKD410	Grey	4.8 mm	3.3 mm	10 mm	18 mm	3,000	200
PKD412	Grey	4.8 mm	3.3 mm	12 mm	20 mm	3,000	200
PKD418	Grey	4.8 mm	3.3 mm	18 mm	26 mm	3,000	200

PKD Cable type: flexible copper, Maximum section: 6 mm²




Type	Colour	Ø	B	P	L	Pack qty	Min. pack qty
PKD612	Yellow	6.3 mm	4 mm	12 mm	20 mm	1,500	100
PKD618	Yellow	6.3 mm	4 mm	18 mm	26 mm	2,000	100

PKD Cable type: flexible copper, Maximum section: 10 mm²




Type	Colour	Ø	B	P	L	Pack qty	Min. pack qty
PKD1012	Red	7.6 mm	5 mm	12 mm	22 mm	1,000	100
PKD1018	Red	7.6 mm	5 mm	18 mm	28 mm	1,000	100

PKD Cable type: flexible copper, Maximum section: 16 mm²




Type	Colour	Ø	B	P	L	Pack qty	Min. pack qty
PKD1612	Blue	8.8 mm	6.4 mm	12 mm	24 mm	800	100
PKD1618	Blue	8.8 mm	6.4 mm	18 mm	28 mm	1,000	100

PKD Cable type: flexible copper, Maximum section: 25 mm²



Type	Colour	Ø	B	P	L	Pack qty	Min. pack qty
PKD25016	Yellow	11.2 mm	7.9 mm	16 mm	30 mm	500	50
PKD25022	Yellow	11.2 mm	7.9 mm	22 mm	36 mm	500	50


PKD Cable type: flexible copper, Maximum section: 35 mm²



Type	Colour	Ø	B	P	L	Pack qty	Min. pack qty
PKD35016	Red	12.7 mm	8.8 mm	16 mm	30 mm	400	50


PKD35025	Red	12.7 mm	8.8 mm	25 mm	39 mm	400	50
----------	-----	---------	--------	-------	-------	-----	----

PKD Cable type: flexible copper, Maximum section: 50 mm²



Type	Colour	Ø	B	P	L	Pack qty	Min. pack qty
PKD50020	Blue	15 mm	11 mm	20 mm	36 mm	300	50
PKD50025	Blue	15 mm	11 mm	25 mm	41 mm	300	50

PKD Cable type: flexible copper, Minimum section: 0.3 mm², Maximum section: 0.5 mm²



Type	Colour	Ø	B	P	L	Pack qty	Min. pack qty
PKD506	White	2.6 mm	1.4 mm	6 mm	12 mm	10,000	500
PKD508	White	2.6 mm	1.4 mm	8 mm	14 mm	10,000	500
PKD510	White	2.6 mm	1.4 mm	10 mm	16 mm	10,000	500