

EW-05F-6

Multi Conductor Cable Cutting and Stripping Machine With Mechanical Claw



Technical data

|                             |                                                                 |
|-----------------------------|-----------------------------------------------------------------|
| Model                       | EW-05F-6                                                        |
| Function                    | Cut, Strip                                                      |
| Conductor cross-section     | 0.75 - 30 mm <sup>2</sup>                                       |
| Core wire stripping         | 2 - 11 cores                                                    |
| Cutting length              | 1 - 99999.9 mm                                                  |
| Cutting length tolerance    | < 0.002 * L (L = cutting length)                                |
| Stripping length (side I)   | Cable jacket - Full strip: 1 - 200 mm - Half strip: 1 - 1000 mm |
| Stripping length (side II)  | Cable jacket - Full strip: 1 - 120 mm - Half strip: 1 - 350 mm  |
| Maximum guide tube diameter | 16 mm                                                           |
| Productivity                | 3500 pcs./h                                                     |
| Blade material              | Imported high speed steel                                       |
| Display mode                | 7-inch touch screen                                             |
| Driving mode                | 16-wheel driving, servo tool holder                             |
| Feeding mode                | By belts                                                        |
| Power supply                | 110, 220 V (50 - 60 Hz)                                         |
| Power                       | 1 kW                                                            |
| Compressed air connection   | 0.5 - 0.7 MPa                                                   |
| Weight                      | 140 kg                                                          |
| Dimension                   | 707 * 590 * 1140 mm                                             |