

# Thin-wall heat shrink tubing

H-2(LS) - Thin-wall heat shrink tubing - 2:1 - Min. shrink temperature 65 °C - Operating temperature up to 125 °C



## Technical specifications

Shrink ratio	: 2:1
Flame retardant	: Yes
Self-extinguishing	: Yes
Adhesive	: No
Operating temperature	: -55 °C up to +125 °C
Minimum shrink temperature	: +65 °C
Minimum full recovery temperature	: +95 °C
Longitudinal change	: 0 up to 10% max.
Material	: Crosslinked polyolefin
Halogen-free	: Yes
Approvals	: RoHS
Available colors	: Black (UV resistant)= ●

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Packaging type
				Reel (meter)
H-2(LS) 1.6/0.8	1.6	0.8	0.50	150
H-2(LS) 2.4/1.2	2.4	1.2	0.50	150
H-2(LS) 3.2/1.6	3.2	1.6	0.50	150
H-2(LS) 4.8/2.4	4.8	2.4	0.50	75
H-2(LS) 6.4/3.2	6.4	3.2	0.60	75
H-2(LS) 9.5/4.8	9.5	4.8	0.60	75
H-2(LS) 12.7/6.4	12.7	6.4	0.60	50
H-2(LS) 16.0/8.0	16.0	8.0	0.60	50
H-2(LS) 19.0/9.5	19.0	9.5	0.80	30
H-2(LS) 25.4/12.7	25.4	12.7	0.90	30
H-2(LS) 32.0/16.0	32.0	16.0	0.90	30
H-2(LS) 38.1/19.0	38.1	19.0	1.00	30
H-2(LS) 50.8/25.4	50.8	25.4	1.10	30