

ASSEMBLY ITEM NUMBER	PART CHARACTERISTICS		
	NUMBER OF POSITION	PANEL MOUNT OPTION	MATERIAL
43020-0200	02	YES	"B"
43020-0201	02	NO	
43020-0400	04	YES	
43020-0401	04	NO	
43020-0600	06	YES	
43020-0601	06	NO	
43020-0800	08	YES	
43020-0801	08	NO	
43020-1000	10	YES	
43020-1001	10	NO	
43020-1200	12	YES	"A"
43020-1201	12	NO	
43020-1400	14	YES	
43020-1401	14	NO	
43020-1600	16	YES	
43020-1601	16	NO	
43020-1800	18	YES	
43020-1801	18	NO	
43020-2000	20	YES	
43020-2001	20	NO	
43020-2200	22	YES	
43020-2201	22	NO	
43020-2400	24	YES	
43020-2401	24	NO	

CKT. NO.	DIM. "A"	DIM. "B"	DIM. "C"	DIM. "D"
2	.152/(3.86)	N/A	.166/(4.21)	.311/(7.90)
4	.270/(6.85)	.118/(3.00)	.284/(7.21)	.429/(10.90)
6	.388/(9.85)	.236/(6.00)	.402/(10.21)	.547/(13.89)
8	.506/(12.85)	.354/(9.00)	.520/(13.21)	.665/(16.89)
10	.624/(15.85)	.472/(12.00)	.638/(16.21)	.783/(19.89)
12	.742/(18.85)	.591/(15.00)	.756/(19.21)	.901/(22.89)
14	.860/(21.85)	.709/(18.00)	.874/(22.20)	1.019/(25.88)
16	.978/(24.85)	.827/(21.00)	.992/(25.20)	1.137/(28.88)
18	1.096/(27.85)	.945/(24.00)	1.110/(28.20)	1.255/(31.88)
20	1.215/(30.85)	1.063/(27.00)	1.229/(31.22)	1.373/(34.87)
22	1.333/(33.85)	1.181/(30.00)	1.347/(34.22)	1.491/(37.87)
24	1.451/(36.85)	1.299/(33.00)	1.465/(37.22)	1.609/(40.87)

NOTES:

- HOUSING MATERIAL:
 - "A" - UNFILLED POLYESTER, RATED UL, 94V-0, COLOR IS BLACK.
 - "B" - UNFILLED NYLON, RATED UL, 94V-0, HALOGEN-FREE, COLOR IS BLACK.
- FINISH: N/A
- PRODUCT SPECIFICATION: PS-43045
- PACKAGING SPECIFICATION: PK-43020-001
- THIS HOUSING MATES WITH MICRO-FIT RECEPTACLE #43025-****
- THIS HOUSING TO BE USED WITH MOLEX MALE TERMINAL #43031-****
- DESIGNED FOR .065/(1.6) MINIMUM TO A .100/(2.54) MAXIMUM THICK PANEL OR PRINTED CIRCUIT BOARD.
- SEE SECTION "D"-D FOR TERMINAL ORIENTATION IN HOUSING.
- PANEL MOUNT FEATURES MUST LOCK ON SIDE OPPOSITE PUNCH SIDE FOR OPTIMUM RETENTION.
- PART CONFORMS TO CLASS "B" REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002. SOME HOUSINGS MAY HAVE A SMALL GATE BLEMISH NEAR THE GATE LOCATION THAT DOES NOT AFFECT FUNCTIONALITY.

SECTION "E"-E" (NO SCALE)

RECOMMENDED PANEL CUT-OUT

SECTION "B"-B"

PLUG WITH OPTIONAL PANEL MOUNTS
ISO VIEW
(8 CIRCUIT SHOWN)

MATED MICRO-FIT CONNECTOR

SECTION "D"-D" WITH TERMINAL (SCALE 8X)

REV	DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
			mm	INCH	IN/MM				
6-12	CKT TO "B"	▽=0	4 PLACES ±---	±---	DRAWN BY	DATE	4:1	METRIC	MICRO-FIT(3.0) 2 THRU 24 CIRCUIT PLUG WITH OPTIONAL PANEL MOUNTS
7	EC NO: UCP2012-4465	▽=0	3 PLACES ±---	±.010	AFG	1993/01/07			
8	DRAWN:STROH	▽=0	2 PLACES ±0.25	±.014	BAP	1993/01/07			
9	CHKD:SSOUSEK	▽=0	1 PLACE ±0.35	±---	APPROVED BY	DATE			
10	APPR:FSM TH		0 PLACE ±	±	FSM TH	2010/11/18			
			ANGULAR ±1/2°		MATERIAL NO.				
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART				
					THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				

DOCUMENT NO. SDA-43020-****

SHEET NO. 1 OF 1

10_frame_D_P_ME_T
Rev. G 2012/01/11