

2.3 Dual wall heat shrink tubing

H-5(3X)-F - Dual wall heat shrink tubing - 3:1 - With adhesive - Operating temperature up to 135 °C



Technical specifications

Brand	: WKK (produced by Hongshang)
Shrink ratio	: 3:1
Flame retardant	: Yes
Self-extinguishing	: Yes
Adhesive	: Yes
Operating temperature	: -55 °C up to +135 °C
Minimum shrink temperature	: +70 °C
Minimum full recovery temperature	: +110 °C
Longitudinal change	: 0 up to 10% max.
Material	: Crosslinked co-extruded adhesive lined polyolefin
Halogen-free	: No
Approvals	: UL E204071 (only for black), CSA, RoHS, MIL-SPEC
Available colors	: Black (UV resistant)= ● White= ○ Red= ● Blue= ● Yellow= ● Green= ● Purple= ● Brown= ● Grey= ●

Scan this QR code for article numbers, current prices and stock information and to order directly.

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Packaging type		
				Reel (meter)	Minibox (meter)	Length piece (mm)
H-5(3X)-F 3.0/1.0	3.0	1.0	1.00	150	5.0	1.220
H-5(3X)-F 4.8/1.5	4.8	1.5	1.00	75	4.0	1.220
H-5(3X)-F 6.0/2.0	6.0	2.0	1.00	75	3.5	1.220
H-5(3X)-F 9.0/3.0	9.0	3.0	1.35	50	3.0	1.220
H-5(3X)-F 12.0/4.0	12.0	4.0	1.65	30	2.5	1.220
H-5(3X)-F 19.0/6.0	19.0	6.0	2.10	30	2.0	1.220
H-5(3X)-F 24.0/8.0	24.0	8.0	2.35	30	1.5	1.220
H-5(3X)-F 30.0/10.0	30.0	10.0	2.40	30	-	1.220
H-5(3X)-F 40.0/13.0	40.0	13.0	2.40	30	-	1.220

H-5(4X)-F - Dual wall heat shrink tubing - 4:1 - With adhesive - Operating temperature up to 135 °C



Technical specifications

Brand	: WKK (produced by Hongshang)
Shrink ratio	: 4:1
Flame retardant	: Yes
Self-extinguishing	: Yes
Adhesive	: Yes
Operating temperature	: -55 °C up to +135 °C
Minimum shrink temperature	: +70 °C
Minimum full recovery temperature	: +110 °C
Longitudinal change	: 0 up to 10% max.
Material	: Crosslinked co-extruded adhesive lined polyolefin
Halogen-free	: No
Approvals	: UL E204071, CSA, RoHS, MIL-SPEC
Available color	: Black (UV resistant)= ●

Scan this QR code for article numbers, current prices and stock information and to order directly.

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Packaging type	
				Reel (meter)	Length piece (mm)
H-5(4X)-F 4.0/1.0	4.0	1.0	1.00	150	1.220
H-5(4X)-F 6.0/1.5	6.0	1.5	1.00	75	1.220
H-5(4X)-F 8.0/2.0	8.0	2.0	1.00	75	1.220
H-5(4X)-F 12.0/3.0	12.0	3.0	1.35	50	1.220
H-5(4X)-F 16.0/4.0	16.0	4.0	1.62	30	1.220
H-5(4X)-F 24.0/6.0	24.0	6.0	2.10	30	1.220
H-5(4X)-F 32.0/8.0	32.0	8.0	2.35	30	1.220
H-5(4X)-F 52.0/13.0	52.0	13.0	2.35	30	1.220